



Strip Gel

Aircraft Paint Remover

- Results in 5 Minutes
- Thick Gel Formula for Vertical Surfaces
- Removes Multiple Layers of Automotive/Industrial Paints and Finishes
- For Professional Use

POR-15® Strip Gel provides a superior aircraft-grade formulation resulting in a highly effective paint remover that quickly lifts the toughest automotive coatings from metal surfaces. Its heavy-bodied consistency provides excellent vertical hold perfect for upright and difficult to reposition projects. The Strip Gel formula is safe for all types of automotive metal.



Aircraft Paint Remover

- Results in 5 Minutes
- Thick Gel Formula for Vertical Surfaces
- Removes Multiple Layers of Automotive / Industrial Paints and Finishes
- For Professional Use

DANGER POISON!
 VAPOR HARMFUL. MAY BE FATAL OR CAUSE BLINDNESS
 IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION.
 Read Cautions and HEALTH HAZARD INFORMATION elsewhere on label.

1 US GALLON 3.78 LITERS

Features:

- Fast-acting
- Excellent verticle hold
- Aircraft-grade strength
- Removes automotive and industrial paints and finishes
- Safe for all types of metal
- Removes multiple layers of coatings
- Higly effective
- Saves time

PRODUCT	SIZE	CODE
Strip Gel	Gal.	40501



Technical Data

Strip Gel

Aircraft Paint Remover



TYPICAL PROPERTIES

CONTAINS: Methylene Chloride (75-09-2); Methanol (67-56-1); Ammonia (7664-41-7).

Cannot be made non-poisonous. VOC is less than 50%. This product is non-photochemically reactive.

Physical state and appearance: Liquid

pH: >12

Boiling/condensation point: >40°C (>104°F)

Relative density: 1.09

Vapor pressure: 40 to 46.5kPa (300 to 349 mm Hg)

Vapour density: 2.9 [Air = 1]

Odor: Chlorinated hydrocarbon odor

Solubility: Easy soluble in the following materials: methanol, diethyl ether, n-octanol and acetone.

Insoluble in the following materials: cold water and hot water

Application Information

APPLICATION: Use caution when opening. Contents may be under pressure. For best results apply at temperatures between 60°F and 90°F. Protect hands with chemical resistant gloves and eyes with chemical resistant goggles. Pour remover into a wide mouth metal or glass container. Apply POR-15® Strip Gel liberally, brushing in one direction only with old or chemical resistant paint brush. Apply to one section at a time. Leave on surface until old finish bubbles loose from surface (5 to 15 minutes depending on the number of coats of old finish). Some finishes will not bubble, but soften. Pre-test for removal time. DISCARD BRUSH AFTER USE. Do not use on plastic or synthetic surfaces, in direct sunlight or on hot surfaces. May soften fiberglass. Do not rush the remover, let POR-15® Strip Gel do the work. For final cleanup, use fine steel wool dipped in POR-15® Strip Gel or POR-15® Solvent. Wipe surface thoroughly with clean cloth. Allow surface to thoroughly dry before recoating. Prime or apply POR-15® Rust Preventive Coating to ferrous metal as soon as possible to prevent flash rusting.

Do not use in unventilated areas, basements or small enclosed areas where vapors can accumulate and cause a health hazard. When possible use outdoors. If using indoors, open all windows and doors and maintain good ventilation. Read entire label and product Safety Data Sheet (SDS) available on-line at AbsoluteCoatings.com before use.

NOTE: NOT FOR USE ON AIRCRAFT. This product is not Boeing Certified. Not tested for sandwich corrosion, immersion corrosion or hydrogen embrittlement. May cause hydrogen embrittlement on hardened steel.

DISPOSAL: Clean up rags, papers and waste promptly and move outdoors. Allow solvent to evaporate, then dispose of in metal container in accordance with local, state and federal regulations.

Safety Information

HEALTH HAZARD INFORMATION: Vapor Harmful. Contains methylene chloride which has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. May affect the brain or nervous system causing dizziness, headache or nausea. REDUCES THE BLOOD'S OXYGEN-CARRYING CAPACITY.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contact with flame or hot surface may produce toxic/corrosive gases. Keep away from heat, sparks and flame. Vapor may cause flash fire. Do not smoke. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Extinguish all flames and pilot lights, turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Use this product outdoors, if possible. If you must use indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. If you experience eye watering, headache or dizziness, or if workplace exposure monitoring indicates methylene chloride levels cannot be controlled below the established OSHA exposure limits (29 CFR 1910.1050), then appropriate respiratory protection must be provided. Obtain professional advice before using respiratory protection.

A dust mask does not provide protection against vapors. Do not use in basement or other unventilated area. Do not breathe vapors or mist. Avoid contact with eyes, skin and clothing. Causes eye, nose, throat and skin irritation. Avoid prolonged or repeated contact with skin. May be harmful if absorbed through skin. Wash thoroughly with soap and water after handling. Cannot be made non-poisonous. Use only with adequate ventilation. Poison keep out of reach of children / animals.

FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty breathing, leave area, obtain fresh air. If difficulty continues, get medical assistance immediately. Avoid contact with eyes, skin and clothing. Eye Contact: Immediately flush thoroughly with water for at least 15 minutes, get medical attention at once. Skin Contact: Flush with plenty of water for at least 15 minutes. Wash thoroughly with soap and water. If irritation persists, seek advice of physician. Remove contaminated clothing and shoes. Wash clothing before reuse. Transport and store in upright position only. Never store or transport in an area where sun or heat exposure may cause temperature of product to elevate above normal ambient conditions, this may cause product to expand, causing product to leak or rupture container. If spilled, contain material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Refer to Safety Data Sheet available from your dealer for further safety and handling information.



Absolute Coatings, Inc.
38 Portman Rd, New Rochelle, NY 10801

800-457-6715
www.AbsoluteCoatings.com