# Collinite





## No. ss126 Sapphire Auto Wax

#### -AUTOMOTIVE LIQUID CLEANER-WAX-

- 1. Function: Combination cleaner + protector for exterior vehicle finishes
- Removes surface contaminants caused by time and weathering
- Restores and enhances appearance
- Preserves and protects condition of finish against future weathering/damaging elements
- NOT specifically designed for clean, or otherwise unblemished surfaces
- Contains mild cut cleaning agents/abrasives
- Has ability to remove previously applied layer(s) of wax

#### 2. Recommended for:

- Tarnished/soiled/stained/discolored/weathered auto surfaces
- Light colored clear coat paints (white, silver), fiberglass, gel coat
- Coated, non-coated and non-painted metals; aluminum, chrome, brass, copper, and stainless steel
- Auto, marine, aeronautical/aircraft, and RV application

### 2a. NOT for use on:

- Dark clear coat paint (blacks, navy, red, etc) or painted metals
- Surfaces unmentioned above, as testing has yet to be extensively conducted. Refer to Collinite directly with application inquiries.

## 3. Directions for use:

- · Shake well before using.
- Apply THIN amount of No. ss126 to a small section no larger than 2X2 ft at a time
- Rub well to loosen all tarnish, oxidation etc. Reapply as necessary until surface is free of embedded contaminants
- Before product dries, polish off with clean, dry soft cloth or microfiber towel

## 3a. Application/Tech Tips:

- Use in a well-ventilated area with protective eyewear a nd gloves
- Applicator pads and removal towels should be clean, free of residue
- Do NOT apply wax to sections larger than recommended before removing, as prolonged drying or cure times
  may lead to wax hardening on surface; causing streaking or difficulty for some users to remove properly. User
  assumes risk if recommended cure times are exceeded.
- Drying times may vary based on conditions (air and surface temperature, humidity, wind, sunlight etc).

# Collinite

- Avoid applying in extreme temperatures (over 80 degrees F or less than 55 degrees F). Surface temperatures should feel lukewarm-room temperature to the touch. Do not apply if surface feels cold or hot to the touch.
- Safe to use with machine buffer <u>if experienced</u>. Check machine manufacturer's speed/pad specifications for auto cleaner-waxes that contain a mild-cut abrasive. NOT recommended for dark clear coats.
- If additional wax protection is desired, follow up No. ss126 application (after removal) with one of Collinite's last step wax products; No. 845, 925, 915, 885, 476.

## 4. Additional

- Store product at room temperature away from fire or flame
- Discard product if exposed to frozen temperatures
- · Keep cap or lid on product when not in use
- Do not alter product's composition or original packaging in any way

## 5. Safety

See MSDS

## 6. Physical

Product consistency: milky/creamy liquid

Sizes available: 16 fluid oz and 1 gallon (128 fluid oz)