

# Collinite



## *No.885 Fleetwax*

### **-LAST STEP MARINE PASTE WAX-**

#### **1. Function:** Last step product for use on exterior vehicle finishes

- Enhances look and appearance
- Preserves and protects condition of finish against weathering/elements.
- Not designed to clean, remove or otherwise mask blemishes or imperfections; swirls, scratches, oxidation, etc that are embedded in finish such that regular wash will not remove.
- Contains no abrasives or cleaners

#### **2. Recommended for:**

- CLEAN, unblemished gel coat, fiberglass, clear-coat, lacquer, and single stage auto paint, and painted, non-coated/coated metals (aluminum, chrome, brass, copper, stainless steel).

#### **2a. NOT for use on:**

- Rubber, black trim, vinyl, glass or non-painted plastic
- Surfaces NOT recommended above, as testing has yet to be extensively conducted. Refer to Collinite directly with application inquiries.

#### **3. Directions for use:**

- Apply THIN coat of wax with foam pad or synthetic sponge to a CLEAN section no larger than 2X2 ft at a time.
- When wax begins to dry (light, hazy residue will appear on surface), remove with dry microfiber towel or cotton cloth.

#### **3a. Application/Tech Tips:**

- Use in a well-ventilated area with protective eyewear and gloves
- Applicator pads and removal towels should be clean, free of residue
- If surface is soiled with contaminants (stains/dirt/oxidation etc) that cannot be removed with a regular wash, first use Collinite's No. 920 Fiberglass Boat Cleaner.
- Only apply to a CLEAN surface; washed, and free of blemishes, discoloration or other imperfections like swirls or scratches. A clean/properly-prepped surface will ease the application/removal process; improving spread and increasing durability of wax's bond.

# Collinite

- Do NOT apply wax to entire boat or vehicle, or sections larger than recommended before removing, as prolonged drying or cure times may lead to wax hardening on surface; causing streaking or difficulty for some users to remove properly. User assumes risk if recommended cure times are exceeded.
- Drying times may vary based on conditions (air and surface temperature, wind, humidity, sunlight etc).
- Avoid applying in direct sunlight, or extreme temperatures (over 80 degrees F or less than 55 degrees F). Surface temperatures should feel lukewarm-room temperature to the touch. Do not apply if surface feels cold or hot to the touch.
- Safe to use with machine buffer if experienced. Check machine manufacturer's speed/pad specifications for last step protective paste waxes that contain no cleaners, abrasives or filling agents.
- To further maintain the look and durability of the waxed finish between wax applications, use a boat wash soap that is pH neutral and gentle on the finish with no grease-cutting properties. Avoid heavy detergents or low-grade soaps.

## 4. Additional

- Store product at room temperature away from fire or flame
- Discard product if exposed to frozen temperatures
- Keep cap or lid on product when not in use
- Do not alter product's composition or original packaging in any way
- **SPREAD/COVERAGE:** Depending on finish and conditions, one 12 oz can for every 6-12 runabout-sized boats (15-20 ft)

## 5. Safety

See MSDS

## 6. Physical

Product consistency: hard paste

Sizes available: 12 oz