

7696 Route 31 Lyons NY 14489

Voice: 315.946.1213 Fax: 315.946.4456

www.caswellplating.com

CASWELL REPROCHROME® PLATING INSTRUCTIONS

Caswell REPROCHROME® is a unique Cobalt/Tungsten plating solution that provides a bright, chrome-like plate onto copper, brass, nickel, steel and most other ferrous and non-ferrous metals. For best corrosion resistance and shine, we recommend plating in copper, then nickel before REPROCHROME® plating.

REPROCHROME® comes pre-mixed and ready for use. Just add REPROCHROME® brightener at the rate of 3ml per 1000ml (0.40 fl oz per 1 Gal) of REPROCHROME® Starter (but don't add it yet)

Operating Instructions:

- Use HDPE or PVC plastic tank. Clean and rinse thoroughly with DISTILLED WATER before use.
- 2. Install stainless steel anodes and maintain at least a 1:1 ratio of anode surface area to part surface area.
- 3. Install pump agitation to keep solution moving.
- 4. Pour REPROCHROME® starter into tank to required level.
- 5. Heat bath to 140 deg F with a stainless steel or titanium heater plus thermostat.
- 6. Plate a cleaned dummy part (scrap metal as big as you can find that will fit in the tank) at 5V DC for 5-15 mins.
- 7. Remove dummy and add REPROCHROME® brightener at the rate of 3ml per 1000ml (0.40 fl oz per 1 Gal) no point using your brightener on the dummy part.
- 8. Install part to be plated.
- 9. Plate at 0.07 amps per square inch of part surface area at approx 5 volts.
- 10. Plate for 1-2 minutes

Some shadowing and discoloration is normal in a brand new bath. Plate dummy parts until an even color is achieved. This might also occur if bath is not used for periods of time.

Solution pH is 9.9-10.2. Read pH at 140F with pump agitation.

Troubleshooting:

Durling	Onlytten
Problem	Solution
No plating in low areas or patchy plating	Add REPROCHROME® Starter to replenish.
	Increase current.
Dark Deposit	Add REPROCHROME® Starter or adjust pH
Light Deposit	Increase temperature and/or current
Milky Solution with plating defects	pH out of range or replenisher additions too
	large. Add water or replace solution.

Theoretical bath life is 50 sq ft per 1 gallon of REPROCHROME® bath.